

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 January 2003 (30.01.2003)

PCT

(10) International Publication Number
WO 03/008126 A1

(51) International Patent Classification⁷: B21D 7/08

(21) International Application Number: PCT/IT01/00381

(22) International Filing Date: 18 July 2001 (18.07.2001)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): NUOVA
CML S.R.L. [IT/IT]; Via Annunziata, I-03030 Piedimonte
San Germano (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): CAPORUSSO,
Alessandro [IT/IT]; Via Annunziata, I-03030 Piedimonte
San Germano (IT).

(74) Agent: GRISTINA, Giorgio; Studio Rag. Giorgio
Gristina, Via delle Quattro Fontane, 29, I-00184 Roma
(IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA,
ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.


(54) Title: A HYDRAULIC CIRCUIT FOR LINEARLY DRIVING A MOVABLE ROLLER-HOLDER SLIDER OF A PIPE BENDING MACHINE



(57) Abstract: A hydraulic circuit for linearly driving a movable roller-holder slider of a pipe bending machine, comprising a hydraulic cylinder (5) whose piston rod is connected to a slider holding a movable roller, the cylinder being fed with pressurized fluid from a reservoir (16) by a pump (15), through a three-position four-way valve (18), a check valve (12, 13) and an interposed throttling valve (19), that is operated to generate an increased pressure in said low pressure chamber of the hydraulic cylinder (5) in order to slow down the slider holding the upper roller in its primary motion when a programmable interval is reached from said predetermined position for each working pass.



WO 03/008126 A1



Description

A hydraulic circuit for linearly driving a movable roller-holder slider of a pipe bending machine

5

Technical field

This invention relates to a hydraulic circuit for linearly driving a movable roller-holder slider of a pipe bending machine. The pipe bending machine can be of any kind, both symmetrical or asymmetrical. For simplicity and clarity sake a pyramidal, symmetrical pipe bending machine is referred to below.

10

Background Art

An upper roller among three rollers of an existing pyramidal, symmetrical pipe bending machine is generally mounted on a slider that is vertically movable by a hydraulic cylinder. The hydraulic circuit ensuring that the movable roller-holder slider is linearly driven comprises a hydraulic cylinder whose rod is connected to the roller-holder slider. The hydraulic cylinder has an upper chamber and a lower chamber, both chambers communicating with respective ducts of pressurized fluid that is feed from a reservoir by a pump. A three-position four-way valve and a check valve operate on both ducts. These valves, as well as the pump, are controlled by an electronic control unit.

15

20

The roller-holder slider travels downward in a primary motion to a bending position and upward in a return motion to a rest position.

25

As known, pipes or other section bars are bent among the three rollers of a pipe bending machine through an operation including one pass or more with a result of the desired deformation. In order to obtain this deformation, specially when one workpiece or more has to be bent exactly with the same bending radius, one must keep for every workpiece the same position of the movable roller with respect to the fixed rollers, wherein the bending operation is performed.

30

The valves in the hydraulic circuit, controlled by the electronic control unit, do not ensure an exact positioning of the hydraulic cylinder rod at the required vertical position in the various passes. This is owing to a number of forces in action,

among which the frictional force in the downward motion, the resistance of the material of the workpiece to be bent, the active forces of the piston of the hydraulic cylinder, the seal deflecting force, the elastic force of the piston ring, the counteracting differential thermodynamic force, the time constant of the control
5 response of the electromagnetic valve, the viscosity of the hydraulic fluid and its non homogeneity due to the presence of air having a coefficient of compressibility different from that one of the hydraulic fluid.

In order to remedy the imprecision of the actual point of halting the movable roller-holder slider, mechanical stops have been used in the past that can ensure,
10 without ascertainable error, the exact position of the movable roller in which a respective bending pass has to be performed.

However, to set the points of halting by mechanical stops is a troublesome operation, that involves an added effort and waste of time, in particular when deformations with great radiuses of curvature have to be performed.

15 Further, in the past, in order to solve the problem, complicate hydraulic circuits provided with proportional valves involving increased costs have been used.

Disclosure of the invention

The present invention aims to overcome the drawbacks above mentioned.

20 In particular, an object of the present invention is to allow a pipe bending machine to operate, determining with precision the position of pipe bending while a position of bending can be set without requiring a mechanical stop device.

Therefore, the present invention provides a hydraulic circuit for linearly driving a movable roller-holder slider of a pipe bending machine, comprising a
25 hydraulic cylinder whose piston rod is connected to a slider holding a movable roller that travels in its primary motion to a predetermined position for each pass of one or more passes of working operation of a workpiece to be bent and in its return motion to a rest position, the hydraulic cylinder having a high pressure chamber and a low pressure chamber, both chambers communicating with respective ducts of
30 pressurized fluid fed from a reservoir by a pump, ducts on which a three-position four-way valve and a check valve operate, further comprising, between said valves, a throttling valve, that is operated by an electromagnet to generate an increased

pressure in said low pressure chamber of the hydraulic cylinder in order to slow down the slider holding the upper roller in its primary motion when a programmable interval is reached from said predetermined position for each working pass.

5 The invention will be now described with reference to its preferred embodiment, although it has to be understood that modifications can be made to the invention without departing from the spirit thereof, referring to the figures of the accompanying drawing, in which:

Figure 1 shows a diagrammatic side view of a partially opened pipe bending machine, to which a hydraulic circuit according to the invention is applied;

Figure 2 shows a diagram of hydraulic circuit according to the invention; and

Figures 3 to 6 show different operative positions of two valves of the hydraulic circuit according to the invention in its operation on the pipe bending machine.

Referring to the drawing, the general appearance of a pipe bending machine, generally denoted as 1, is shown in Figure 1. The pipe bending machine 1 is equipped with a hydraulic circuit according to the invention.

20 The pipe bending machine shown by way of example is of a symmetrical pyramidal kind. It has frontally (on the right hand side in Figure 1) a pair of fixed lower rollers (only one roller, denoted as 2, is shown) and an upper roller 3. The upper roller 3 is mounted conventionally on a slider (not shown) that is connected to a piston rod 4 diagrammatically represented in Figure 2. The piston rod 4 is a part of a hydraulic cylinder 5 having an upper chamber 6 and a lower chamber 7.

25 Owing to the motion of the piston rod 4, the slider holding the upper roller 3 is movable downward during a primary motion from a general position indicated by an axis *g* to a predetermined position of axis *l*, as shown in an explanatory way in Figure 1. The bending operation of a workpiece (not shown) is performed during a travel including one pass or more. In every pass, said predetermined position of axis
30 *l* is selected for each workpiece. If e.g. it is intended that two equal workpieces to be bent are worked by two passes, and an equal end position of pipe bending, but a

different intermediate position is chosen for every workpiece to be bent, two workpieces with different dimensional characteristics would be obtained.

One would appreciate the importance that bending positions are achieved exactly as much as possible.

5 As constructively and diagrammatically shown in Figures 1 and 2 respectively, the upper chamber 6 and the lower chamber 7 of the hydraulic cylinder 5 are communicating through their ports 8 and 9 with respective ducts 10 and 11 of pressurized fluid, and a pilot-operated to close check valve, that consists of a pair of single-acting valve 12 and 13, is provided.


10 A pressurized fluid, in general oil for hydraulic circuits, is fed from a reservoir 14 through a motor-pump unit 15. As best shown in Figure 2, at least a filter 16 and a pilot-operated safety valve 17 are provided in the circuit of the pump. Further conventionally, a three-position four-way valve 18 operates on both ducts 10 and 11. The valves, as well as the pump, are controlled by an electronic control
15 unit (not shown).

According to the invention, a throttling valve 19, that is controlled by an electromagnet, is joined to the valve 18 on the same ducts 10 and 11.

Also the throttling valve 19 is operated by said electronic control unit (not shown) to generate a back pressure in the lower chamber 7 of the hydraulic cylinder
20 5. In fact, in the primary motion, i.e. in the downward travel of the movable roller 3, when the predetermined bending position which is defined by the axis *l* of the movable roller is approaching, it is suitable to slow down the slider holding the upper roller 3 so that the last one can reach exactly the bending position. This deceleration, e.g. from the position of axis *h* is obtained by operating, as desired, the
25 throttling valve 19 in order to gradually slow down the movable roller travelling downward, up to the complete closure of the valve in the desired end position for the bending pass that is performed.

The interval *h-l* inside which the slow down is performed is programmable according to the desired precision and so on.

30 This deceleration is obtained through the combined operation of the three-position four-way valve 18 and the throttling valve 19, as shown in Figures 3 to 6.



In these figures a streamline of high pressure fluid coming from the pump unit 15 is indicated as A, and a streamline of low pressure fluid returning from the hydraulic cylinder 5 operating the slider holding the upper roller 3 is indicated as B.

Referring to Figure 3, the three-position four-way valve 18 and the throttling valve 19 are shown in an arrangement in which the high pressure streamline A goes to the high pressure chamber 6 of the cylinder, and the low pressure streamline B indicates the return flow exiting the low pressure chamber 7. The throttling device, denoted as 20, of the throttling valve 19 is in a non working arrangement and remains in this position until the predetermined position of axis *h* of the movable roller 3 is reached (Figure 1). From this position the throttling device 20 is operated, as shown in Figure 4. The streamline B is diverted to a bypass 21, where the rate of flow is reduced.

Consequently, there is a pressure increasing in the low pressure chamber 7 of the cylinder 5. As a result, the downward travel of the movable roller 3 is slowed until the position of axis *l* is reached in which the flow is stopped, and both chambers 6 and 7 are under the same operating pressure. In the same time, all slacks are taken up, including air balls that are the decisive factor of error by having a compressibility different from that one of the hydraulic fluid. Now, the three-position four-way valve 18 and the throttling valve 19 are brought to a rest arrangement shown in Figure 5.

In order to return the movable roller 3 to its former position of axis *g*, the three-position four-way valve 18 and the throttling valve 19 are brought to an arrangement shown in Figure 6 in which the throttling device 20 is not working. Now, as for the throttling valve 19, the arrangement of Figure 3 is repeated, while the three-position four-way valve 18 performs the backflow. Through this operation, the chamber 7 of the cylinder 5 becomes the high pressure chamber, while the chamber 6 becomes the low pressure chamber.

The throttling valve 18 can be a unidirectional valve. In alternative, the throttling valve 18 can be a bi-directional valve, in order to assure a slow down in both primary and return motions.

The present invention has been described with reference to its specific embodiment, but it would be expressly understood that modifications, addition

and/or omissions can be made without departing from the spirit of invention as defined in the enclosed claims.

Claim

1. A hydraulic circuit for linearly driving a movable roller-holder slider of a pipe bending machine, comprising an hydraulic cylinder whose piston rod is connected to a slider holding a movable roller that travels in its primary motion to a
5 predetermined position for each pass of one or more passes of working operation of a workpiece to be bent and in its return motion to a rest position, the hydraulic cylinder having a high pressure chamber and a low pressure chamber, both chambers communicating with respective ducts of pressurized fluid fed from a reservoir by a pump, ducts on which a three-position four-way valve and a check
10 valve operate, characterized in that the hydraulic circuit further comprises, between said valves, a throttling valve, that is operated by an electromagnet to generate an increased pressure in said low pressure chamber of the hydraulic cylinder in order to slow down the slider holding the upper roller in its primary motion when a programmable interval is reached from said predetermined position for each
15 working pass.




FIG. 1

2/4




FIG. 2

3/4




FIG. 3




FIG. 4

4/4




FIG. 5




FIG. 6

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B21D7/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B21D F15B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 173 598 B1 (CAPORUSSO MARIO ET AL) 16 January 2001 (2001-01-16) the whole document	1
A	DE 22 57 368 A (SCHWARZE RIGOBERT) 12 June 1974 (1974-06-12) the whole document	1
A	DE 197 51 504 A (STAERK LIESELOTTE ; STAERK RUEDIGER (DE)) 23 July 1998 (1998-07-23) the whole document	1
A	US 4 918 958 A (GLOMB REINER ET AL) 24 April 1990 (1990-04-24) the whole document	1

☐ Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

5 March 2002

Date of mailing of the international search report


18/03/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ritter, F



INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 01/00381

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6173598	B1	16-01-2001	IT RM970310 A1	23-11-1998
			BR 9803336 A	03-11-1999
			CA 2238159 A1	23-11-1998
			CN 1202399 A	23-12-1998
			EP 0879655 A2	25-11-1998
			JP 3177216 B2	18-06-2001
			JP 11010240 A	19-01-1999
			KR 270759 B1	01-12-2000
			TW 421612 B	11-02-2001
			US 5970770 A	26-10-1999
DE 2257368	A	12-06-1974	DE 2257368 A1	12-06-1974
DE 19751504	A	23-07-1998	DE 29620391 U1	23-01-1997
			DE 19751504 A1	23-07-1998
US 4918958	A	24-04-1990	DE 3505739 A1	21-08-1986
			AT 56377 T	15-09-1990
			DE 3579695 D1	18-10-1990
			WO 8604837 A1	28-08-1986
			EP 0215006 A1	25-03-1987
			JP 62501894 T	30-07-1987

